



Pirouette Water Wheel Nozzle



Brass + Stainless steel
Straighteners



As with the “Hibiscus” fountain nozzle, the theory behind the operation of this rotating nozzle is based on the waterwheel.

Using only water pressure, a continuous effect of movement is created without additional mechanical or electrical devices.

No movement is necessary to generate this watery swaying motion.

A swaying motion that brings to mind mesmerizing Arab belly dancing.

WIND RESISTANCE				
SPLASH				
NOISE LEVEL				
VISIBILITY				
WATER APPEARANCE	CLEAR			



TECHNO WATER DESIGNS
The Art of Water

Design Studio & Workshop • Unit 4, 33 Jade Drive Molendinar 4214

Ph • +617 5597 5882

E • info@techno-waterdesigns.com.au

W • www.techno-waterdesigns.com.au

PIROUETTE WATER WHEEL NOZZLE

Dimensions						Performance														
Reference	Connection	Length (mm) B	Length (mm) C x D	Jets number	Weight (kg)	Pressure (m.c.a)		2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,5	7,0	8,0	9,0		
PJ 23412	¾" M NPT/ BSP	79	128x128	4+1	0,40	Height (m)	H	1,50	2,00	2,25	2,50									
							h	1,25	1,50	1,75	1,75									
						Diam. (m)		2,2	2,3	2,7	3,2									
						Flow	l/min	25	28	30	32									
							m³/h	1,50	1,68	1,98	1,92									
PJ 21511	1½" M NPT/ BSP	106	280x280	16+1	1,62	Height (m)	H			3,25	3,50	4,00	4,25	4,50						
							h			2,25	2,50	2,75	3,00	3,25						
						Diam. (m)				2,8	4,0	4,5	5,0	5,3						
						Flow	l/min			95	100	105	110	117						
							m³/h			5,7	6,0	6,3	6,6	7,0						
PJ 22016	2" M NPT/ BSP	148	521x521	24+1	3,80	Height (m)	H								5,00	5,50	6,00	7,00		
							h								3,15	3,50	4,00	4,50		
						Diam. (m)									7,5	8,0	8,5	9,0		
						Flow	l/min								217	225	245	255		
							m³/h								13,02	13,50	14,70	15,30		

